

OPTIONAL ACCESSORIES FOR VCX 130 AND VCX 130 PB

CONVERTER CLAMP

Securely supports 1¼" (32 mm) diameter converter on support stand with ½" (13 mm) diameter support rod. Chemical-resistant reinforced plastic.

Part No. 830-00118



SUPPORT STAND

Black enameled 5½" x 9" (140 x 229 mm) cast-iron base and ½" (13 mm) diameter, 24" (610 mm) long zinc-plated rod.

Part No. 830-00109



FOOTSWITCH

For hands-free operation. Compatible with VCX 130 and VCX 130 FSJ only. 10' (3 m) cable with plug.

Part No. 830-00004



HAND HELD FREQUENCY METER

Check the frequency of energized probes, converters and boosters.

Frequency range: 10.00 - 99.99 kHz

Part No. 833-00012



SOUND ABATING ENCLOSURE

Even though ultrasonic vibrations are above the human audible range, ultrasonic processing produces a high pitched noise in the form of harmonics, which emanate from the vessel walls and the fluid surface. The sound abating enclosure permits extended processing without discomfort by reducing the sound by 35 db. The probe/converter assembly is supported by the converter clamp, and the converter cable is fed through the ¾" (19 mm) opening at the top. Side access ports accommodate the tubing delivering the coolant and the sample to the processing vessel while the door is closed. The unit is faced on the exterior with white laminate, and lined on the interior with white waterproof polyethylene noise abating material. The access door permits observation during treatment and protects the operator against accidental splashing. Support rod and converter clamp are included.

Outside dimensions: (H x W x D) 20" x 12" x 12" (510 x 300 x 300 mm).

Part No. 630-0451

